



## INTERPLAN 150

<b>DESCRIPTION</b>	Water rinsable, non-crazing cleaner. INTERPLAN 150 has been formulated for application on synthetic materials, polycarbonate, (un) painted substrates, aluminium and fabrics.	
<b>SPECIFICATIONS</b>	-MS10.0033 Class W	
<b>APPLICATION</b>	For general cleaning purpose of all synthetic materials, aluminium and fabrics. Excellent for use after assembly of painted parts that need cleaning from handling and assembly stains. Leaves a fresh and inviting scent. For cleaning painted surfaces dilute as much as required.	
<b>OPTIMAL WORKING CONDITIONS</b>	Temperature	15-35°C (60-95°F)
	Relative humidity	10-80%
<b>PRECAUTIONS</b>	Use rubber gloves. See SDS for further detailed information.	
<b>DENSITY</b>	1.0 kg/L	8.3 lb. /gal.
<b>PACKAGING</b>	5L	
<b>STORAGE STABILITY</b>	In closed containers and at T=5-25°C (41-77°F): 5 years.	

### **WWW.HSH-AERO.COM**

The information contained in this document is given in good faith by HSH and based on HSH current knowledge. It is only an indication and is in no way binding particularly as regards infringement or prejudice to third parties through the use of our products. The information must on no account be used as a substitute for necessary prior tests which alone can ensure that a product is suitable for a given use.